

JACK SINGLE A-TRACK-TIF



GENERAL INFO

JA**F**/**C**/9**CT**/**R** - Jack

JA2**F**/9**CT**/**R** – Jack²

ATJA**F**/9**CT**/**R** - Jack AT

AT2JA**F**/9**CT**/**R** - Jack 2 AT

ATLJA**F**/9**CT**/**R** - Jack AT LOW

ATL2JA**F**/9**CT**/**R** - Jack 2 AT LOW

F = Finish / C = ceiling base / CT = Color temp. / R = Reflector

Jack is available with O4, I4 and I6 ceiling base.

Jack² always needs a Jackpoint option to plug into.

With Jackpoint Stretch ceiling option there is no canopy visible when Jack² is plugged in.

SPECIFICATIONS

LED LM OUTPUT	420 lm
POWER CONS.	4,2W
DRIVE CURRENT	48Vdc
COLOR TEMP	2700K / 3000K
CRI/GAI	>90
REFLECTOR	16° - 25° - 48°
FINISH	Black (BL) / White (WH) / Brushed Ano (BA) / Bronze (BR) / Gun Metal Bronze (GM) / Champagne (CH) / Canon Fusil (CF)
REMARK	Options: C6004 – Jack Honeycomb option only dali dimmable