

NALA IM6



GENERAL INFO

References

NM1BR/IM6/927/24 Nala IM6 Bronze 927 24°
NM1BR/IM6/927/36 Nala IM6 Bronze 927 36°
NM1BR/IM6/927/60 Nala IM6 Bronze 927 50°
NM1BR/IM6/930/24 Nala IM6 Bronze 930 24°
NM1BR/IM6/930/36 Nala IM6 Bronze 930 36°
NM1BR/IM6/930/50 Nala IM6 Bronze 930 50°

NM1CH/IM6/927/24 Nala IM6 Champagne 927 24°
NM1CH/IM6/927/36 Nala IM6 Champagne 927 36°
NM1CH/IM6/927/60 Nala IM6 Champagne 927 50°
NM1CH/IM6/930/24 Nala IM6 Champagne 930 24°
NM1CH/IM6/930/36 Nala IM6 Champagne 930 36°
NM1CH/IM6/930/50 Nala IM6 Champagne 930 50°

NM1GM/IM6/927/24 Nala IM6 Gun Metal Bronze 927 24°
NM1GM/IM6/927/36 Nala IM6 Gun Metal Bronze 927 36°
NM1GM/IM6/927/60 Nala IM6 Gun Metal Bronze 927 50°
NM1GM/IM6/930/24 Nala IM6 Gun Metal Bronze 930 24°
NM1GM/IM6/930/36 Nala IM6 Gun Metal Bronze 930 36°
NM1GM/IM6/930/50 Nala IM6 Gun Metal Bronze 930 50°

SPECIFICATIONS

LED	COB
LED LM OUTPUT	644lm
POWER CONS.	9W
DRIVE CURRENT	700mA / 13Vdc max
COLOR TEMP	2700k / 3000k
CRI/GAI	95
REFLECTOR	24° / 36° / 50°
FINISH	Bronze (BR) / Gun Metal Bronze (GM) / Champagne (CH)
ADJUSTABLE	45° x 355°
CUT-OUT	Ø 45 mm
CLASS	III