

NALA O4



GENERAL INFO

References

NA1BR/O4/927/24 *Nala O4 Bronze 927 24°*

NA1BR/O4/927/36 *Nala O4 Bronze 927 36°*

NA1BR/O4/927/60 *Nala O4 Bronze 927 50°*

NA1BR/O4/930/24 *Nala O4 Bronze 930 24°*

NA1BR/O4/930/36 *Nala O4 Bronze 930 36°*

NA1BR/O4/930/50 *Nala O4 Bronze 930 50°*

NA1CH/O4/927/24 *Nala O4 Champagne 927 24°*

NA1CH/O4/927/36 *Nala O4 Champagne 927 36°*

NA1CH/O4/927/60 *Nala O4 Champagne 927 50°*

NA1CH/O4/930/24 *Nala O4 Champagne 930 24°*

NA1CH/O4/930/36 *Nala O4 Champagne 930 36°*

NA1CH/O4/930/50 *Nala O4 Champagne 930 50°*

NA1GM/O4/927/24 *Nala O4 Gun Metal Bronze 927 24°*

NA1GM/O4/927/36 *Nala O4 Gun Metal Bronze 927 36°*

NA1GM/O4/927/60 *Nala O4 Gun Metal Bronze 927 50°*

NA1GM/O4/930/24 *Nala O4 Gun Metal Bronze 930 24°*

NA1GM/O4/930/36 *Nala O4 Gun Metal Bronze 930 36°*

NA1GM/O4/930/50 *Nala O4 Gun Metal Bronze 930 50°*

SPECIFICATIONS

LED

COB

LED LM OUTPUT

644lm

POWER CONS.	9W
DRIVE CURRENT	700mA / 13Vdc max
COLOR TEMP	2700k / 3000k
CRI/GAI	95
REFLECTOR	24° / 36° / 50°
FINISH	Bronze (BR) / Gun Metal Bronze (GM) / Champagne (CH)
ADJUSTABLE	45° x 355°
CLASS	III