




POWERLINE OPTIONS

POWERLINE ON & SUSPENSION

	DESCRIPTION	REFERENCE	REMARKS
MOUNTING OPTIONS			
	SUSPENSION SET		
	suspension set 2.000 mm suspension set 5.000 mm	AT/PS/2000 AT/PS/5000	
	WALL BRACKET OPTION / up to 2.260 mm		
	wall bracket set (2pcs mounted)	PL/WBS	Other RAL colours on request.
	POWERLINE MOUNTED ON 3F TRACK (available for non-dim ON versions)		
	Double 3F adaptor option white Double 3F adaptor option black	PL/D3F/W PL/D3F/B	Double 3F option available for lengths up to 2.260 mm
	Single rotor 3F adaptor white Single rotor 3F adaptor black	PL/S3F/W PL/S3F/B	Single rotor 3F option available for lengths up to 1.140 mm
MODULE OPTIONS			
	OPTIONAL MODULES		
	Emergency module 3 hrs. Motion detector incl. profile 100 mm Ambient light/motion sensor / DALI incl. remote* Standalone DALI / detection sensor* Casambi DALI build-in* Push button dimming / DALI versions	PL/EM PL/MT PL/ALS PL/SAD PL/CAS PL/PBA	* only available in DALI versions Top mounted for suspension/ end-cap position ON versions
	EXTRA CIRCUIT PER METER		
		PL/EC	