


# POWERLINE CEILING



REFERENCE	DIM	POWER CONS (W)	LUMEN OUTPUT (lm)	LENGTH (mm)
<b>Powerline ON ceiling 2.540 mm</b>				
PL_/2540/___/ND/O	-	58,5	7.080	2.540
PL_/2540/___/A/O	1-10 V	58,5	7.080	2.540
PL_/2540/___/D/O	DALI	58,5	7.080	2.540
<b>Powerline ON ceiling 2.820 mm</b>				
PL_/2820/___/ND/O	-	65	7.860	2.820
PL_/2820/___/A/O	1-10 V	65	7.860	2.820
PL_/2820/___/D/O	DALI	65	7.860	2.820
<b>Powerline ON ceiling 3.100 mm</b>				
PL_/3100/___/ND/O	-	71,5	8.660	3.100
PL_/3100/___/A/O	1-10 V	71,5	8.660	3.100
PL_/3100/___/D/O	DALI	71,5	8.660	3.100
<b>Powerline ON ceiling 3.380 mm</b>				
PL_/3380/___/ND/O	-	78	9.450	3.380
PL_/3380/___/A/O	1-10 V	78	9.450	3.380
PL_/3380/___/D/O	DALI	78	9.450	3.380
<b>Powerline ON ceiling 3.660 mm</b>				
PL_/3660/___/ND/O	-	83,5	10.240	3.660
PL_/3660/___/A/O	1-10 V	83,5	10.240	3.660
PL_/3660/___/D/O	DALI	83,5	10.240	3.660
<b>Powerline ON ceiling 3.940 mm</b>				
PL_/3940/___/ND/O	-	91	11025	3.940
PL_/3940/___/A/O	1-10 V	91	11025	3.940
PL_/3940/___/D/O	DALI	91	11025	3.940
<b>Powerline ON ceiling 4.220 mm</b>				
PL_/4220/___/ND/O	-	97,5	11.812	4.220
PL_/4220/___/A/O	1-10 V	97,5	11.812	4.220
PL_/4220/___/D/O	DALI	97,5	11.812	4.220
<b>Powerline ON ceiling 4.500 mm</b>				
PL_/4500/___/ND/O	-	104	12.600	4.500
PL_/4500/___/A/O	1-10 V	104	12.600	4.500
PL_/4500/___/D/O	DALI	104	12.600	4.500