

POWERLINE RECESSED

	DESCRIPTION	REFERENCE	REMARKS
MOUNTING OPTIONS			
	PROFILE RECESSED WITH PC COVER		
	anodised aluminium white matt RAL 9016 tex black matt RAL 9005 tex	PLRA/001 PLRW/001 PLRB/001	Maximum length 4.500 mm. Other RAL colours on request.
	PROFILE RECESSED WITH ALU COVER		
	anodised aluminium white matt RAL 9016 tex black matt RAL 9005 tex	PLRA/002 PLRW/002 PLRB/002	Maximum length 4.500 mm. Other RAL colours on request.
	BLACK TRANSPARENT DIFFUSOR		
	Black transparent diffusor	PL/BTC	Maximum length single piece 4.500 mm.
	END CAP (1 pc.)		
	anodised aluminium white matt RAL 9016 tex black matt RAL 9005 tex	PLR/EC/A PLR/EC/W PLR/EC/B	
	MOUNTING BRACKET RECESSED / EACH		
	0 mm - 2.260 mm = 2 brackets 2.260 mm - 3.380 mm = 3 brackets 3.380 mm - 4.500 mm = 4 brackets	PLR/MBR	
	PROFILE CONNECTORS		
	profile connector 90° profile connector 180° (straight)	PL/90 PL/180	
SERVICES			
	PROFILE CUT/SAW CUT		
	profile cut	PL/PC	one 90° profile needs 2 cuts