

POWERLINE SUSPENSION



PROFILE COLORS	CRI	CCT	HEIGHT	WIDTH
A anodised aluminium	+80	2.700 K / 827	75	38
W white matt texture RAL9016	+80	3.000 K / 830	75	38
B black matt texture RAL9005	+80	4.000 K / 840	75	38
REMARK: - DALI version = PUSH DIM compatible - other RAL colors on request				
REFERENCE BUILDER: PL_A/580/830/ND/O				
REFERENCE	DIM	POWER CONS (W)	LUMEN OUTPUT (lm)	LENGTH (mm)
Powerline suspended 580 mm				
PL_/580/___/ND/S	-	13	1.575	580
PL_/580/___/A/S	1-10 V	13	1.575	580
PL_/580/___/D/S	DALI	13	1.575	580
Powerline suspended 860 mm				
PL_/860/___/ND/S	-	19,5	2.362	860
PL_/860/___/A/S	1-10 V	19,5	2.362	860
PL_/860/___/D/S	DALI	19,5	2.362	860
Powerline suspended 1.140 mm				
PL_/1140/___/ND/S	-	26	3.150	1.140
PL_/1140/___/A/S	1-10 V	26	3.150	1.140
PL_/1140/___/D/S	DALI	26	3.150	1.140
Powerline suspended 1.420 mm				
PL_/1420/___/ND/S	-	32,5	3.920	1.420
PL_/1420/___/A/S	1-10 V	32,5	3.920	1.420
PL_/1420/___/D/S	DALI	32,5	3.920	1.420
Powerline suspended 1.700 mm				
PL_/1700/___/ND/S	-	39	4.725	1.700
PL_/1700/___/A/S	1-10 V	39	4.725	1.700
PL_/1700/___/D/S	DALI	39	4.725	1.700
Powerline suspended 1.980 mm				
PL_/1980/___/ND/S	-	45,5	5.500	1.980
PL_/1980/___/A/S	1-10 V	45,5	5.500	1.980
PL_/1980/___/D/S	DALI	45,5	5.500	1.980
Powerline suspended 2.260 mm				
PL_/2260/___/ND/S	-	52	6.300	2.260
PL_/2260/___/A/S	1-10 V	52	6.300	2.260
PL_/2260/___/D/S	DALI	52	6.300	2.260