


POWERLINE SUSPENSION



REFERENCE	DIM	POWER CONS (W)	LUMEN OUTPUT (lm)	LENGTH (mm)
Powerline suspended 2.540 mm				
PL_/2540/___/ND/S	-	58,5	7.080	2.540
PL_/2540/___/A/S	1-10 V	58,5	7.080	2.540
PL_/2540/___/D/S	DALI	58,5	7.080	2.540
Powerline suspended 2.820 mm				
PL_/2820/___/ND/S	-	65	7.860	2.820
PL_/2820/___/A/S	1-10 V	65	7.860	2.820
PL_/2820/___/D/S	DALI	65	7.860	2.820
Powerline suspended 3.100 mm				
PL_/3100/___/ND/S	-	71,5	8.660	3.100
PL_/3100/___/A/S	1-10 V	71,5	8.660	3.100
PL_/3100/___/D/S	DALI	71,5	8.660	3.100
Powerline suspended 3.380 mm				
PL_/3380/___/ND/S	-	78	9.450	3.380
PL_/3380/___/A/S	1-10 V	78	9.450	3.380
PL_/3380/___/D/S	DALI	78	9.450	3.380
Powerline suspended 3.660 mm				
PL_/3660/___/ND/S	-	83,5	10.240	3.660
PL_/3660/___/A/S	1-10 V	83,5	10.240	3.660
PL_/3660/___/D/S	DALI	83,5	10.240	3.660
Powerline suspended 3.940 mm				
PL_/3940/___/ND/S	-	91	11025	3.940
PL_/3940/___/A/S	1-10 V	91	11025	3.940
PL_/3940/___/D/S	DALI	91	11025	3.940
Powerline suspended 4.220 mm				
PL_/4220/___/ND/S	-	97,5	11.812	4.220
PL_/4220/___/A/S	1-10 V	97,5	11.812	4.220
PL_/4220/___/D/S	DALI	97,5	11.812	4.220
Powerline suspended 4.500 mm				
PL_/4500/___/ND/S	-	104	12.600	4.500
PL_/4500/___/A/S	1-10 V	104	12.600	4.500
PL_/4500/___/D/S	DALI	104	12.600	4.500